Ramp Capacity Ratings

There are many methods that are used to give a ramp its loading capacity rating. Do not be fooled by the numbers. Our ramps are rated using a footprint 6" wide by 16" long. Pressure is applied to the center of the ramp with this footprint. We then apply a three times safety factor to arrive at the weight our ramps are capable of loading safely. This gives you a true capacity rating that has the safety of you and your employees at heart. Ask your ramp supplier how they arrive at their capacity rating.

LB10 Series

Side Step Mount (Bifold Design)

Model Number (style-width-length)	Capacity (lbs)	Weight (lbs)
LB10-24-54	1000	64
LB10-24-72	1000	76
LB10-24-81	1000	82
LB10-30-54	1000	74
LB10-30-72	1000	86
LB10-30-81	1000	92
LB10-36-54	1000	84
LB10-36-72	1000	96
LB10-36-81	1000	102

LB20 Series

Flat Mount (Bifold Design)

Model Number (style-width-length)	Capacity (lbs)	Weight (lbs)
LB20-24-54	1000	72
LB20-24-72	1000	84
LB20-24-81	1000	90
LB20-30-54	1000	82
LB20-30-72	1000	94
LB20-30-81	1000	100
LB20-36-54	1000	92
LB20-36-72	1000	104
LB20-36-81	1000	110

LT30 Series

Flat Mount (Trifold Design)

Model Number (style-width-length)	Capacity (lbs)	Weight (lbs)
LT30-24-110	1000	110
LT30-30-110	1000	125
LT30-36-110	1000	140

LS50 Series

Heavy Duty Straight Design

Model Number (style-width-length)	Capacity (lbs)	Weight (lbs)
LS50-24-54	1000	37
LS50-24-63	1000	43
LS50-24-72	1000	49
LS50-24-81	1000	56
LS50-24-90	1000	62
LS50-24-99	750	69
LS50-24-108	750	75
LS50-24-117	750	81
LS50-24-126	750	88
LS50-24-135	750	94
LS50-30-54	1000	42
LS50-30-63	1000	49
LS50-30-72	1000	56
LS50-30-81	1000	64
LS50-30-90	1000	71
LS50-30-99	750	78
LS50-30-108	750	85
LS50-30-117	750	92
LS50-30-126	750	99
LS50-30-135	750	107
LS50-36-54	1000	47
LS50-36-63	1000	56
LS50-36-72	1000	64
LS50-36-81	1000	72
LS50-36-90	1000	80
LS50-36-99	750	88
LS50-36-108	750	96
LS50-36-117	750	105
LS50-36-126	750	113
LS50-36-135	750	121